

10 800h

## General Data

Artikelnummer	34319271
Bestellzeichen	NL-T8 UV 30W/254 G13 RO
EAN-Faltschachtel	4058075502642
Versandeinheit in Stk.	25
EAN Umkarton (Versandeinheit)	4058075502659
Brutto-Gewicht Versandeinheit in kg	3.789
Länge Versandeinheit in m	0.93
Breite Versandeinheit in m	0.15
Höhe Versandeinheit in m	0.15
Product weight	120 g
Produktstatus	● PhaseOut

## Electric Parameters

Lamp power	30.0 W
Lamp voltage	220-240 V

## Light Application Parameters

Type of UV radiation	UV-C
UV power	12.6 W

## Service Life

Average life	10800 h
--------------	---------

## Specification

Diameter	26 mm
Total length max.	895 mm
radiator length (glass)	808 mm
Burning position	Random
Lamp shape	Tube, double-ended
Base	G13

## Notes on Operation

Burning position	Random
Generating ozone	Nein
Suitable for air disinfection	Ja
Suitable for water disinfection	Ja


## Notes

Disinfection lamp (UV-C), Operation in suitable fixture only. Please, note installation instructions. Attention: radiation can harm skin and eyes!

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Sockelübersicht



G13  
IEC/EN 60061-1  
sheet 7004-51-8

### Besonderheiten



### Allgemeine Hinweise

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

# Disinfection lamp UV-C

NL-T8 UV 30W/254 G13

**Radium**

## Sicherheitshinweise

Attention: NL-T8 UV-C emit short-wave UV radiation. The radiation can cause corneal inflammation and / or conjunctivitis of the eye, as well as damage to the skin. IN ORDER TO PREVENT HEALTH DAMAGE CAUSED BY RADIATION (injuries, burns, illnesses), ANY CONTACT WITH RADIATION direct or indirect (via reflections) MUST BE AVOIDED. NL-T8 UV-C lamps are only to be used in devices designed for this purpose. The safety instructions of the device manufacturer must be observed. Under no circumstances should this lamp be used for general lighting. The product contains mercury. If the lamp breaks, follow the appropriate rules of conduct and dispose of it properly after use.

All technical data without guarantee.